

MSDS # 59.00

Ammonium Sulfide 20-24%**Section 1: Product and Company Identification****Ammonium Sulfide 20-24%****Synonyms/General Names:** N/A**Product Use:** For educational use only**Manufacturer:** Columbus Chemical Industries, Inc., Columbus, WI 53925.**24 Hour Emergency Information Telephone Numbers****CHEMTREC (USA): 800-424-9300****CANUTEC (Canada): 613-424-6666**

ScholarAR Chemistry; 5100 W. Henrietta Rd, Rochester, NY 14586; (866) 260-0501; www.Scholarchemistry.com

Section 2: Hazards Identification*Clear, yellow liquid; strong sulfur or hydrogen sulfide odor.***HMIS (0 to 4)**

Health	3
Fire Hazard	3
Reactivity	0

DANGER! Flammable and toxic vapors. Strong body tissue irritant and inhalation hazard. Reaction with acid will liberate poisonous and flammable hydrogen sulfide.

Target organs: Central nervous system, lungs, eyes, skin, mucous membranes

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Section 3: Composition / Information on Ingredients

Ammonium sulfide, (12135-76-1), 20-24%

Water, (7732-18-5), 64-69%

Ammonium Hydroxide (1336-21-6), 11-12%

Section 4: First Aid Measures*Always seek professional medical attention after first aid measures are provided.***Eyes:** Immediately flush eyes with excess water for 15 minutes, lifting lower and upper eyelids occasionally.**Skin:** Immediately flush skin with excess water for 15 minutes while removing contaminated clothing.**Ingestion:** Call Poison Control immediately. **Do not induce vomiting.** Rinse mouth with cold water. Give victim 1-2 cups of water or milk to drink.**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration.**Section 5: Fire Fighting Measures**

Flammable solution. When heated to decomposition, emits acrid fumes of ammonia and sulfur dioxide.

Protective equipment and precautions for firefighters: Use foam or dry chemical to extinguish fire.

Firefighters should wear full fire fighting turn-out gear and respiratory protection (SCBA). Cool container with water spray. Material is not sensitive to mechanical impact or static discharge.

**Section 6: Accidental Release Measures**

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Remove all ignition sources and ventilate area. Contain spill with sand or absorbent material and place material in a sealed bag or container for disposal. Wash spill area after pickup is complete. See Section 13 for disposal information.

Section 7: Handling and Storage**White****Handling:** Use with adequate ventilation and do not breathe dust or vapor. Avoid contact with skin, eyes, or clothing. Wash hands thoroughly after handling.**Storage:** Store in Corrosive Area [White Storage] with other corrosive items. Store in a dedicated corrosive cabinet. Store in a cool, dry, well-ventilated, locked store room away from incompatible materials.**Section 8: Exposure Controls / Personal Protection**Use ventilation to keep airborne concentrations below exposure limits. Have approved eyewash facility, safety shower, and fire extinguishers readily available. Wear chemical splash goggles and chemical resistant clothing such as gloves and aprons. Wash hands thoroughly after handling material and before eating or drinking. Use NIOSH-approved respirator with an acid/organic cartridge. Exposure guidelines Hydrogen Sulfide: OSHA PEL: 10 ppm; ACGIH TLV: 10 ppm, STEL: 15 ppm. Ammonia: OSHA PEL: 35 mg/m³; ACGIH TLV: 17 mg/m³, STEL: 24 mg/m³.

Section 9: Physical and Chemical Properties

Molecular formula	(NH ₄) ₂ S.	Appearance	Clear, yellow liquid.
Molecular weight	68.15.	Odor	Hydrogen sulfide odor.
Specific Gravity	0.99 g/ml @20°C.	Odor Threshold	N/A.
Vapor Density (air=1)	2.3.	Solubility	Complete.
Melting Point	0°C.	Evaporation rate	N/A. (<i>Butyl acetate = 1</i>).
Boiling Point/Range	100°C.	Partition Coefficient	N/A. (<i>log P_{ow}</i>).
Vapor Pressure (20°C)	450 mm Hg.	pH	9.5, basic.
Flash Point:	32°C (90°F).	LEL	4%.
Autoignition Temp.:	N/A.	UEL	46%.

N/A = Not available or applicable

Section 10: Stability and Reactivity**Stability:** Stable under normal conditions of use and storage. Avoid heat and ignition sources.**Incompatibility:** Bases, aluminum, copper, zinc, strong acids, strong oxidizers.**Shelf life:** Indefinite if stored properly.**Section 11: Toxicology Information****Acute Symptoms/Signs of exposure:** **Eyes:** Redness, tearing, itching, burning, damage to cornea, conjunctivitis, loss of vision. **Skin:** Redness, blistering, burning, itching, tissue destruction with slow healing. **Ingestion:** Nausea, vomiting, burning, diarrhea, ulceration, convulsions, shock. **Inhalation:** Coughing, wheezing, shortness of breath, headache, spasm, inflammation and edema of bronchi, pneumonitis.**Chronic Effects:** Repeated/prolonged skin contact may cause thickening, blackening or cracking. Repeated eye exposure may cause corneal erosion or loss of vision.**Sensitization:** none expected*Ammonium Sulfide: LD50 [oral, rat]; N/A; LC50 [rat];N/A; LD50 Dermal [rabbit]; N/A**Ammonia: LD50 [oral, rat]; 530 mg/kg; LC50 [rat];N/A; LD50 Dermal [rabbit]; N/A**Material has not been found to be a carcinogen nor produce genetic, reproductive, or developmental effects.***Section 12: Ecological Information****Ecotoxicity (aquatic and terrestrial):**

Ecological impact has not been determined.

Section 13: Disposal Considerations

Check with all applicable local, regional, and national laws and regulations. Local regulations may be more stringent than regional or national regulations. Small amounts of this material may be suitable for sanitary sewer disposal after being neutralized to pH 7.

Section 14: Transport Information

DOT Shipping Name:	Ammonium Sulfide Solution .	Canada TDG:	Ammonium Sulfide Solution .
DOT Hazard Class:	8, (6.1)(3), pg II .	Hazard Class:	8, (6.1)(3), pg II .
Identification Number:	UN2683 .	UN Number:	UN2683 .

Section 15: Regulatory Information**EINECS:** Not Listed .**WHMIS Canada:** Not WHMIS Controlled.**TSCA:** All components are listed or are exempt.**California Proposition 65:** Not listed .*The product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.***Section 16: Other Information****Current Issue Date:** January 23, 2009

Disclaimer: Scholar Chemistry and Columbus Chemical Industries, Inc., ("S&C") believes that the information herein is factual but is not intended to be all inclusive. The information relates only to the specific material designated and does not relate to its use in combination with other materials or its use as to any particular process. Because safety standards and regulations are subject to change and because S&C has no continuing control over the material, those handling, storing or using the material should satisfy themselves that they have current information regarding the particular way the material is handled, stored or used and that the same is done in accordance with federal, state and local law. S&C makes no warranty, expressed or implied, including (without limitation) warranties with respect to the completeness or continuing accuracy of the information contained herein or with respect to fitness for any particular use.